

Schedule										
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Lumens Per Lamp	Light Loss Factor	Wattage
	SL12	3	Visionaire Lighting LLC	ODN-2-L-T4-80LC-3-3K-UNV AM XX C5/H5 WSC20 RNTS 4R 11 16 343 T4R XX VA110L D2 4 XX	25 in D x 22.5 in H LED LUMINAIRE		1	10983	0.9	178
	SL2	2	Visionaire Lighting LLC	ODN-2-L-T2-80LC-3-3K-UNV AM XX C5/H5 WSC20 RNTS 4R 11 16 343 T4R XX VA110L S1 4 XX	25 in D x 22.5 in H LED LUMINAIRE		1	11514	0.9	89
	WP1	2	Visionaire Lighting LLC	ODN-2-L-T4-80LC-3-3K-UNV AM XX C5/H5 WSC20 VA1100L WM XX	25 in D x 22.5 in H LED LUMINAIRE		1	10983	0.9	89
	WP2	7	Lithonia Lighting	WST LED P2 30K VW MVOLT	WST LED, Performance package 2, 3000 K, visual comfort wide, MVOLT	LED	1	3511	0.9	25

Note
1.FIXTURE TYPE SL1, SL12 AND SL2 ARE SHOWN POLE MOUNED AT 18' ABOVE FINISHED GRADE (16' POLE, 2' ABOVE GRADE BASE)
2.FIXTURE TYPE WP1 IS SHOWN WALL MOUNTED AT 23' ABOVE FINISHED GRADE.
3.FIXTURE TYPE WP2 IS SHOWN WALL MOUNTED AT 12' ABOVE FINISHED GRADE.
4.ALL SITE FIXTURE SHALL BE 3000K PER TOWN REQUIREMENTS.
5.ALL SITE FIXTURE SHALL BE DARK SKY COMPLIANT.



Plan View
Scale - 1" = 30ft

